

# TECHNICAL DATA

## INDIGO LF-2



	LF2 3000kg 305x139	LF2 3000kg 305x159	LF2 3000kg 355x169	LF2 3000kg 405x159	LF2 3000kg 405x179	LF2 3500kg 455x179
<b>Dimensions/weight</b>						
Total weight (kg)	3000	3000	3000	3000	3000	3500
Empty weight (kg)	700 *	740	764	805 *	835 *	983 *
Payload (kg)	2300	2260	2236	2195	2165	2017
Weight class 3500 kg. Unloaded weight	+ 20	+ 22	+23	+ 22	+ 24	0
Parabolic suspension including shock absorbers 3500kg	+ 78	+ 82	+ 84	+ 82	+ 86	0
Aluminum profile floor	+ 3	+ 4	+ 6	+ 6	+ 7	+ 7
Without full-length tailgate	- 85	- 104	- 110	- 104	- 116	- 116
2 access ramps 195cm high in place of the tailgate	+ 35	+ 18	+ 11	+ 18	+ 12	+ 12
Length of box inside (cm)	[A] 304	304	354	404	404	454
Inner box width (cm)	[B] 139	159	169	159	179	179
Drawbar length (cm)	[C] 156	156	156	156	156	156
Total length (cm)	[D] 489	489	539	589	589	639
Total width (cm)	[E] 198	218	228	218	238	238
Total height (cm)	[F] 145	145	145	145	145	145
Loading platform height (cm)	[G] 35	35	35	35	35	-
Flat loading height (with parabolic suspen	[G] 41,5	41,5	41,5	41,5	41,5	41,5
Coupling height (cm)	[H] 42,5	42,5	42,5	42,5	42,5	-
Coupling height (with parabolic suspensio	[H] 46	46	46	46	46	46
Sidewall height	[I] 19,5	19,5	19,5	19,5	19,5	19,5
Access angle: tailgate 120/150, access ramps 200	16° / 13° / 10°	16° / 13° / 10°	16° / 13° / 10°	16° / 13° / 10°	16° / 13° / 10°	-
Access angle (with parabolic springs): tailgate 120/150, access ramps 200	20° / 16° / 12°	20° / 16° / 12°	20° / 16° / 12°	20° / 16° / 12°	20° / 16° / 12°	20° / 16° / 12°
Tire size	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C	195/50R13C
Number of tie-down points	10	10	10	10	10	10

<b>Options / weights</b>	
Spoon rest	+ 18 kg
Winch with winch bracket	+ 15 kg
Height tailgate 117 cm	
Height access ramps 195 cm width 48 cm	

Dimensions in cm., weight in kg

\* Dimensions and weights may vary, design changes reserved

\* approximate weight

