Wheel bolts Specifications:

| Screw-thread | Scope | Max. Torque | |
|--------------|---------|-------------|--|
| Mm | Mm | Mm Nm | |
| M 12 x 1,5 | 17 (19) | 80 - 90 | |
| M 14 x 1,5 | 19 | 110 - 120 | |

Optimal tire pressure:

The optimum tire pressure depends on the type of tire and can be done at any garage be called. Do not use any other tires than HAPERT Trailers or first ask them or their authorized HAPERT dealer.

| Tire size | Tire pressure | | Max. load |
|-------------|---------------|-----|-----------|
| | BAR | PSI | KG. |
| 155/80/R13 | 2,9 | 42 | 500 |
| 165R13C | 4,5 | 65 | 710 |
| 185/70R13 | 3 | 44 | 650 |
| 175R14C | 4,5 | 65 | 775 |
| 185R14C | 4,5 | 65 | 900 |
| 155/70R12C | 6,5 | 95 | 900 |
| 195/50R13C | 6,5 | 95 | 900 |
| 195/55R10C | 6,2 | 90 | 700 |
| 205/70/R15C | 3,8 | 55 | 900 |
| 145/70R13 | 3 | 44 | 425 |
| 18.5x8.5-8 | 3,4 | 50 | 425 |
| 185/70R13C | 6 | 85 | 950 |